

5mm Soundstop SL Click

Acoustical SPC Click Data Sheet

Product Specifications	Description
Overall Thickness	5mm=(Includes 1mm IXPE Acoustical Sound Pad)
Wear Layer	8-mil, 12-mil, 20-mil
Core Material	5mm thickness: 4mm Core with a 1mm IXPE Acoustical SoundPad. Features 4G Locking System for Extra Dimensional Stability
Finish/Upgrades	Armor Guard Surface Protection-Tested by Intertek Laboratories, Painted Bevel Edges
Dimensions	6"x48", 7"x48", 9"x48"
Installation	Floating or with adhesive
Product Type	SPC Click with a 1mm IXPE Acoustical Soundmat
Acoustical Testing	STC61, IIC54, HIIC63
Adhesive-(Optional)	Sar5000, Mapei ECO399
Transitions	T-Molding, Reducer, End Cap, Stair Nosing, Quarter Round, Quarter Round, Inside Corner Moldings

5mm: Sizes & Systems: Container

www.advancedflooringc.com

Product Specifications	Quantities
Pieces Per Carton	10
Sq Ft Per Carton	24
Sq Ft Per Pallet	1152
Sq Ft Per Container	23039

Why use Innovato Soundstop SL SPC Click?

Benefits	Description:
Functionality:	The Soundlock-I SPC Click Collection is designed for use in Apartments, hotels, or any multi-story building that wants to use our Acoustical SPC Click to replace a soundmat below gypsum saving time and money.
Acoustical Performance	IIC of 54 meets or exceeds most acoustical requirements
Highest Performance of Commercially Graded Materials	All of our Products have gone through the strictest testing measures for long term performance, acoustics and durability
Complimentary Products	Transitions with Matching Colors-(Quarter Round, Shoe Molding, Stair Nosing), Matching 2mm Glue Down for 1 st floor applications
Passes Testing	ASTMF1700, ASTME648, ASTME663, ASTMF137, ASTMF1514, ASTMF1515, ASTMF2199, ASTME90 & ASTME492