

LUXE TILE

SPECIFICATIONS

PRODUCT

INSTALLATION	FLOATING CLICK / UNILIN
WEAR LAYER	20 MIL
OVERALL THICKNESS (CORE + PADDING)	6.5 MM / IXPE
FINISH	DIAMONDGUARD™ / HEALTHGUARD™ / EMBOSSED
EDGE	PAINTED BEVEL

PACKAGING

PLANK SIZE	12" X 24"
PLANKS/CARTON	12
SF/CARTON	24.03
CARTONS/PALLET	48
SF/PALLET	1,153.44
PALLETS/CONTAINER	20
SF/CONTAINER	2,3068.8

PREFORMANCE

ASTM F2055 SIZE	PASS
ASTM F386 THICKNNESS	PASS
ASTM F2055 SQUARENESS	PASS
ASTM F1914 RESIDUAL INDENTATION	PASS
ASTM F137 FLEXIBILTY	PASS
ASTM F2199 DIMENISONAL STABILITY	PASS
ASTM F925 CHEMICAL RESISTANCE	PASS
ASTM F1514 RESISTANCE TO HEAT	PASS
ASTM F1515 RESISTANCE TO LIGHT	PASS
ASTM F 970 STATIC LOAD LIM	PASS
CERTIFIED LOW EMITTING PRODUCT	MEETS GUIDELINES
INDOOR AIR QUALITY	MEETS GUIDELINES
INDOOR SOUND TRANSMISSON TEST	IIC: 68 (test condition: 6" concrete slab with drop ceiling)



DIAMONDGUARD™
FINISH



HEALTHGUARD™
FINISH



100% WATERPROOF



PET AND CHILD FRIENDLY



STRONG AND DURABLE



FLOOR SCORE CERTIFIED



PROP 65 COMPLIANT