

## 4.5mm Soundstop: Acoustical Glue Down LVT

**Size:** 18"x18", 20"x20", 24"x24", 36"x36"

**Wear Layer:** 20-mil

**Texture:** Embossed in Register, Deep Embossed

**Thickness:** 4.5mm (including a 1.5mm Sound Pad)

**Collections:** Acosutical Stone/Tile

**Type:** Soundstop Acoustical Glue Down LVT

Description	Results
<b>ASTMF1700</b> -(ASTMF2055, ASTM F386, ASTM F410, ASTM F2055, ASTM F1914, ASTM F137, ASTM F2199, ASTM F925, ASTM F2199, ASTM F1515, ASTM F1514, Certificate of Compliance)	Pass
<b>ANSIA.137 Dynamic Co-efficient of Friction</b>	Average DCOF .44
<b>ASTME648 Critical Radiant Flux of Floor Covering Systems</b>	Meets or exceeds Class 1 rating as specified in NFPA Life Safety Code 101 and IBC 804.2 Classification
<b>ASTME662 Smoke Density</b>	This sample passes the requirements of 450 or less
<b>ASTMF137 Flexibility of Resilient Flooring Materials</b>	Passes 6mm Mandrel
<b>ASTMF925-Resistant to Chemicals</b>	Pass
<b>ASTMF1514 Measuring Heat Stability-(7 Days)</b>	Test requirements of < 8.0 Delta E were met by the tested samples
<b>ASTMF1515-Measuring Light Stability of Flooring by color change</b>	Test requirements of < 8.0 Delta E were met by the tested samples
<b>ASTMF1914-(Short Term Indentation)</b>	Residual Indentation at 40 lbs-0.015 Inch (7.78%)
<b>ASTMF2199-(Dimensional Stability after exposure to heat)</b>	Length--0.008 Inch per 12 inches (-0.07%) Width-0.013 Inch per 12 inches (-0.11%)
<b>ASTMF2055-(Size, Tolerance)</b>	.016 in/lin ft
<b>ASTMF410-Thickness/Wear Layer</b>	Requirement: Commercial .02, Test Result: .011 inch/.26mm

IIC: 61

# Advanced Flooring Concepts

## 3.5 mm Acoustical Glue Down LVT



### Data Sheet - Patent#63/618,154

Advanced Flooring Concepts' Acoustical Glue Down LVT features an integrated acoustical underlayment. Acoustical Stone Tile LVT effectively reduces sound transmitting between upper and lower floors. Available in 5 Authentic stone colors ranging from light to dark, this LVT



- Designed for Upper Floors Replaces
- Acoustical Pad
- Superior Acoustics
- Reduce Installation by 50%

### Loading/Packing Information:

Sq Ft Per Carton: 36 square feet  
Boxes Per Pallet: 45  
Sq Ft Per Pallet: 2,160  
Sq Ft Per Container: 42,530