

2mm/3mm Glue Down LVT: Data Sheet/Specifications

Size: 9"x48", 7.25"x48", 6"x36"

Wear Layer: 6-mil, 8-mil, 12-mil, 20-mil-(3mm Only)

Texture: Deep Embossed


Thickness: 2mm/3mm

Description	Results
ASTMF1700-(ASTMF2055, ASTM F386, ASTM F410, ASTM F2055, ASTM F1914, ASTM F137, ASTM F2199, ASTM F925, ASTM F2199, ASTM F1515, ASTM F1514, Certificate of Compliance	Pass
ANSI A.137 Dynamic Co-efficient of Friction	Average DCOF .44
ASTM E648 Critical Radiant Flux of Floor Covering Systems	Meets or exceeds Class 1 rating as specified in NFPA Life Safety Code 101 and IBC 804.2 Classification
ASTM E662 Smoke Density	This sample passes the requirements of 450 or less
ASTM F137 Flexibility of Resilient Flooring Materials	Passes 6mm Mandrel
ASTM F925-Resistant to Chemicals	Pass
ASTM F1514 Measuring Heat Stability-(7 Days)	Test requirements of < 8.0 Delta E were met by the tested samples
ASTM F1515-Measuring Light Stability of Flooring by color change	Test requirements of < 8.0 Delta E were met by the tested samples
ASTM F1914-(Short Term Indentation)	Residual Indentation at 40 lbs-0.015 Inch (7.78%)
ASTM F2199-(Dimensional Stability after exposure to heat)	Length--0.008 Inch per 12 inches (-0.07%) Width-0.013 Inch per 12 inches (-0.11%)
ASTM F2055-(Size, Tolerance)	.016 in/lin ft
ASTM F410-Thickness/Wear Layer	Requirement: Commercial .02, Test Result: .011 inch/.26mm
Certificate of Compliance	Requirement: Max 1/3 of flat surface area/Test Result: Pass

Glue Down LVT: Made with 100% Virgin material

Sizes & Systems

Thickness	Sq Ft Per Carton	Boxes Per Pallet	Sq Ft Per Pallet	Sq Ft Per Container	Pallets Per Container
2mm	57	48	2700	54000	20
3mm	48	48	2304	46080	20




Amazing Cherry



Breezy Oak



Brookside Oak



Natural White Oak



Bootshake Oak




Butterscotch Oak



Crystal Oak



Opera House Oak




Glazed Hickory



Catalina Grey



Forest Dark



Stadium Oak