


2mm, 2.5mm, 3mm Soundstop SL Glue Down Data Sheet

| Product Specifications | Description |
|------------------------|---|
| Overall Thickness | 2mm, 2.5mm, 3mm |
| Wear Layer | 6-mil, 8-mil, 12-mil, 20-mil |
| Core Material | Dryback/Vinyl |
| Finish | Armor Guard Surface Protection-Tested by Intertek Laboratories |
| Dimensions | 6"x48", 7"x48", 9"x48" |
| Installation | with Adhesive-(Sar5000 or equivalent) |
| Product Type | Glue Down LVT |
| Acoustical Testing | N/A |
| Adhesive | Sar5000, Mapei ECO399 |
| Transitions | T-Molding, Reducer, End Cap, Stair Nosing, Quarter Round, Quarter Round, Inside Corner Moldings |



info@advancedflooringc.com
Ph: (512) 503-2106
www.advancedflooringc.com

2.5mm, 3mm: Sizes & Systems: Container

| Product Specifications | Quantities |
|------------------------|------------|
| Pieces Per Carton | 16 |
| Sq Ft Per Carton | 45 |
| Sq Ft Per Pallet | 2160 |
| Sq Ft Per Container | 46200 |

2mm: Sizes & Systems: Container

| Product Specifications | Quantities |
|------------------------|------------|
| Pieces Per Carton | 20 |
| Sq Ft Per Carton | 48 |
| Sq Ft Per Pallet | 2880 |
| Sq Ft Per Container | 57600 |

Why use Innovato Soundstop SL Glue Down LVT?

| Benefits | Description: |
|--|--|
| Functionality: | The Soundstop SL- Collection is available in a 2mm, 2.5mm, or 3mm thickness, & is a commercially graded LVT perfect for use in any lobby, corridor, or resident areas. With an ultra-realistic wood or stone/ceramic look, your customers will be impressed. |
| Highest Performance of Commercially Graded Materials | All of our Products have gone through the strictest testing measures for long term performance, and durability. Featuring Armor Guard for extreme scratch resistance |
| Complimentary Products | Transitions with Matching Colors-(Quarter Round, Shoe Molding, Stair Nosing), Matching 2mm Glue Down for 1 st floor applications |
| Passes Testing | ASTMF1700, ASTME648, ASTME663, ASTMF137, ASTMF1514, ASTMF1515, ASTMF2199 |